



Technical Data Sheet

NATURAQUA HOLZMASSE BASE

WATERBASED BINDING RESIN

cod. NAT0052



DESCRIPTION

It's a ready to use binding resin for the individual preparation of wood filler. Combined together with wood dust, obtained from sanding, it gives as a result a spreadable paste. The binding resin doesn't change the original colour of the wood, therefore the paste is the same colour as the wood the powder was obtained from.

The paste can be stained or overpainted both with solvent and water based products.

In order to correct the color it's possible to add Holzfarbe Color Concentrate Multipurpose Dye.

FIELDS OF APPLICATION

Individual preparation of filler for repairing wooden surfaces.

CLEANING AND DILUTION

For dilution and cleaning of tools use water.

Characteristics	U.M.	Value
Appearance		liquid
Odour		typical
Color		colorless
Dilution		water
Cleaning of tools		water
Drying time	hours	1, (20°C – 55% RH)
Proportions		1 part resin powder: 3-4 parts resin



HOW TO USE



Mix 3 parts of resin with 1 part of wood powder.



Mix well until the paste is suitable for spreading (the consistency must be that of a paste easily applicable by spatula).



Apply directly onto clean surfaces and make sure the filler fully penetrates any cracks.



The required drying time varies from 45 minutes to 1 hours.



When the filler is completely dry, sand and varnish as required.

TECHNICAL RECOMMENDATIONS

The product can be applied directly on freshly sanded parquet to fill defects and cracks before treating with Borma Parkettlack water-based varnishes for parquet.

In the case in which the affected surface presents small defects, a fluid filler is preferable, while in the case in which the defects are more substantial, a denser filler is recommended, in order to compensate for the natural shrinkage during the drying phase.

PACKAGING

Cod. NAT0052	12 x 1Lt
Cod. NAT0053	2 x 5Lt
Cod. NAT0054	1 x 15Lt
Cod. NAT0055	1 x 20Lt

STORAGE

Store in a cool, well-ventilated place, keep container closed when not in use. Keep away from heat, flames, sparks and other sources of ignition, freezing.

The product has a shelf life of 24 months from the date of production.

WARNINGS

Read the SDS before use.

Observe the safety regulations in force.

Product for professional use.

Our technical data sheets are drawn up on the basis of average results of our tests. However, our technical advice is given in good faith but without guarantee. In fact, different supports, conditions of application, systems, dilutions are an integral part of the final result and often beyond any control. The user must try the products supplied to check if they are suitable for his needs. On our part, the continuity of the chemical-physical characteristics is guaranteed.

Product code: **NAT0052**
Revisione: **01 del 02.05.2025**